

- 70.0 MHz IF SAW Filter / 5.40 MHz Bandwidth
- Revision 0: 20 Aug. 2008


Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operation Temperature Range	°C	-	25	-
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	D1			
Length x Width	mm ²	-	20.0 x 9.8	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	69.90	70.00	70.10
Insertion Loss at Fo	dB	-	15.80	18.00
Group Delay Variation at Fo ±2.4 MHz	nsec	-	135	180
Absolute Delay at Fo	usec	-	1.96	-
Passband Ripple Variation at Fo ±2.4 MHz	dB	-	0.55	1.0
Bandwidth at -1dB	MHz	5.20	5.40	-
Bandwidth at -3dB	MHz	5.70	5.82	-
Bandwidth at -40dB	MHz	-	7.54	7.70
Bandwidth at -50dB	MHz	-	7.70	-
Ultimate Rejection	dB	50	57	-
Temperature Coefficient	ppm/°C	-	-72	-

Notes : (1) With Matching Network (Ref. Testing Environment Circuit as shown below).
Those impedances could be modified with different impedance values and/or structures, if necessary.


Package Dimensions



- ① **TRANSKO:** Brand
- ② **TA07005A:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I	Ground
J	Input
E	Output

Testing Environment





Test Fixture & Values	
Input	L1 = 82 nH , C1 = 15 pF
Output	L2 = 82 nH , C2 = 15 pF
Source/Load Impedance	50 Ω

Frequency Characteristics

Frequency Response



Bandwidth at -1.0 dB

Bandwidth at -3.0 dB




Bandwidth at -40.0 dB

Bandwidth at -50.0 dB




Frequency Response


Ripple Variation Fo±2.4MHz



Group Delay Variation Fo±2.4MHz



Smith Chart



VSWR

