

- 69.99 MHz IF SAW Filter / 16.02 MHz Bandwidth
- Revision 0: 11 MAR. 2009


Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operation Temperature Range	°C	-20	-	70
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	D1			
Length x Width	mm ²	-	20.0 x 9.8	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	69.99	-
Insertion Loss at Fo	dB	-	23.5	26.0
Group Delay Variation (Fo±7.47MHz)	nsec	-	28	50
Absolute Delay at Fo	usec	-	2.17	-
Passband Ripple Variation (Fo±7.47MHz)	dB	-	0.28	0.70
Bandwidth at -1dB	MHz	15.80	16.02	-
Bandwidth at -10dB	MHz	-	16.93	-
Bandwidth at -20dB	MHz	-	17.34	-
Bandwidth at -40dB	MHz	-	17.77	17.95
Ultimate Rejection	dB	50	55	-
Temperature Coefficient	ppm/°C	-	-72	-

Notes : (1) With Matching Network (Ref. Testing Environment Circuit as shown below).
Those impedances could be modified with different impedance values and/or structures, if necessary.


Package Dimensions



- ① **TRANSKO:** Brand
- ② **TA07016B:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I	Ground
J	Input
E	Output

Testing Environment





Test Fixture & Values	
Input	L1 = 82 nH, C1=9pF
Output	L2 = 100 nH
Source/Load Impedance	50 Ω

Frequency Characteristics

Frequency Response



Bandwidth at -1.0 dB

Bandwidth at -10.0 dB




Bandwidth at -20.0 dB

Bandwidth at -40.0 dB




Frequency Response


Ripple Variation Fo±7.47MHz



Group Delay Variation Fo±7.47MHz



Smith Chart



VSWR

