

- 140.0 MHz IF SAW Filter / 15.90 MHz Bandwidth
- Revision 0: 06. May 2009


## Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operation Temperature Range	°C	-10	-	70
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	D1			
Length x Width	mm <sup>2</sup>	-	20.0 x 9.8	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	140.0	-
Insertion Loss at Fo	dB	-	22.50	24.00
Group Delay Variation (Fo±7.5MHz)	nsec	-	40	70
Absolute Delay	usec	-	2.29	2.50
Passband Ripple (Fo±7.5MHz)	dB	-	0.60	1.00
Bandwidth at -1dB	MHz	15.75	15.90	-
Bandwidth at -3dB	MHz	-	16.22	-
Bandwidth at -40dB	MHz	-	17.58	17.75
Bandwidth at -50dB	MHz	-	17.75	-
Ultimate Rejection	dB	50	53	-
Temperature coefficient	ppm/°C	-	-72	-

**Notes :** (1) With Matching Network (Ref. Testing Environment Circuit as shown below).  
Those impedances could be modified with different impedance values and/or structures, if necessary.


## Package Dimensions



- ① **TRANSKO:** Brand
- ② **TA14015A:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I	Ground
J	Input
E	Output

## Testing Environment





Test Fixture & Values	
<b>Input</b>	L1=33nH, C1=15pF
<b>Output</b>	L2=33nH, C2=15pF
<b>Source/Load Impedance</b>	50 Ω

## Frequency Characteristics

**Frequency Response**



**Bandwidth at -1.0 dB**

**Bandwidth at -3.0 dB**



**Bandwidth at -40.0 dB**



**Bandwidth at -50.0 dB**



**Frequency Response**

**Ripple Variation Fo±7.5MHz**

**Group Delay Variation Fo±7.5MHz**



**Smith Chart**

**VSWR**

