

- 160.00 MHz IF SAW Filter / 20.80 MHz Bandwidth
- Revision 1: 16 Jan.. 2013


Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operation Temperature Range	°C	-	25	-
Storage Temperature Range	°C	-45	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	S90			
Length x Width	mm ²	-	13.3 x 6.5	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	160.00	-
Insertion Loss at Fo	dB	-	12.50	15.00
Group Delay Variation at Fo ± 9.5 MHz	nsec	-	50	100
Absolute Delay at Fo	usec	-	0.93	1.20
Passband Ripple Variation at Fo ± 9.5 MHz	dB _{p-p}	-	0.5	1.0
Bandwidth at -1dB	MHz	20.40	20.80	-
Bandwidth at -3dB	MHz	-	21.60	-
Bandwidth at -40dB	MHz	-	25.15	25.60
Ultimate Rejection	dB	37	42	-
Relative Attenuation				
Fo ± 13.0 MHz	dB	40	45	-
Temperature Coefficient	ppm/°C	-	-86	-

Notes : (1) With Matching Network (Ref. Testing Environment Circuit as shown below).
Those impedances could be modified with different impedance values and/or structures, if necessary.


Package Dimensions



- ① **TRANSKO:** Brand
- ② **TF-016001:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

Testing Environment




Test Fixture & Values	
Input	L1 = 27nH
Output	L2 = 56nH, C1 = 27pF
Source/Load Impedance	50 Ω

Frequency Characteristics


Frequency Response

Operating Temperature: +25°C


Bandwidth at -1.0 dB




Bandwidth at -3.0 dB



Bandwidth at -40.0 dB




Relative Attenuation Fo ± 13.0 MHz




Frequency Response


Ripple Variation $F_o \pm 9.5\text{MHz}$



Group Delay Variation $F_o \pm 9.5\text{MHz}$



Smith Chart



VSWR

