

- 62.50 MHz IF SAW Filter / 6.47 MHz Bandwidth
- Revision 0: 17 Mar. 2008


Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operating Temperature Range	°C	-20	-	70
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	V			
Length x Width	mm ²	-	13.3 x 6.5	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	62.5	-
Insertion Loss at Fo	dB	-	9.30	11.00
Temperature Coefficient	ppm/°C	-	-86	-
Amplitude Ripple within fo ±2.5 MHz	dB _{p-p}	-	0.30	0.60
Group Delay Variation within fo ±2.5 MHz	nsec	-	70	120
Absolute Delay at Fo	µsec	-	1.23	-
Bandwidth at -1.0 dB	MHz	6.00	6.47	-
Bandwidth at -3.0 dB	MHz	-	7.15	-
Bandwidth at -40.0 dB	MHz	-	10.00	10.50
Relative Attenuation:				
Lower Sidelobe	dB	48	52	-
Upper Sidelobe	dB	40	45	-

Notes : (1) With Matching Network (Ref. Testing Environment Circuit as shown below).
Those impedances could be modified with different impedance values and/or structures, if necessary.


Package Dimensions



- ① **TRANSKO:** Brand
- ② **TL06206A:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

Testing Environment




Test Fixture & Values	
Input	L1=82nH , L2=27nH
Output	C1=330pF, L3=180nH
Source/Load Impedance	50 Ω


Frequency Characteristics

Frequency Response


Bandwidth at -1.0 dB




Bandwidth at -3.0 dB



Bandwidth at -40.0 dB



Wide-Band




Frequency Response


Ripple Variation Fo±2.5MHz



Group Delay Variation Fo±2.5MHz



Smith Chart



SWR

