

- 62.50 MHz IF SAW Filter / 19.7 MHz Bandwidth
- Revision 0: 30 Jan. 2008


## Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operating Temperature Range	°C	-	25	-
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	V			
Length x Width	mm <sup>2</sup>	-	13.3 x 6.5	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	62.5	-
Insertion Loss at Fo	dB	-	13.9	15.0
Temperature Coefficient	ppm/°C	-	-86	-
Amplitude Ripple within fo ±9.32 MHz	dB <sub>p-p</sub>	-	0.4	0.7
Group Delay Variation within fo ±9.32 MHz	nsec	-	35	60
Absolute Delay at Fo	µsec	-	1.11	-
Bandwidth at -1.0 dB	MHz	-	19.7	-
Bandwidth at -3.0 dB	MHz	20.2	20.3	-
Bandwidth at -40.0 dB	MHz	-	23.4	24.0
Relative Attenuation:				
Lower Sidelobe	dB	45	48	-
Upper Sidelobe	dB	45	48	-

**Notes :** (1) With Matching Network (Ref. Testing Environment Circuit as shown below).  
Those impedances could be modified with different impedance values and/or structures, if necessary.


## Package Dimensions



- ① **TRANSKO:** Brand
- ② **TL06219A:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

## Testing Environment




Test Fixture & Values	
<b>Input</b>	L1=6.8nH , L2=82nH
<b>Output</b>	L3=150nH , C1=22pF
<b>Source/Load Impedance</b>	50 Ω


## Frequency Characteristics

### Frequency Response


**Bandwidth at -1.0 dB**




**Bandwidth at -3.0 dB**



**Bandwidth at -40.0 dB**




**Wide-Band**




**Frequency Response**


**Ripple Variation Fo±9.32MHz**



**Group Delay Variation Fo±9.32MHz**



**Smith Chart**



**SWR**

