

- 65.0 MHz IF SAW Filter / 6.16 MHz Bandwidth
- Revision 0: 16 Jun. 2010


## Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operating Temperature Range	°C	-20	-	70
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	V			
Length x Width	mm <sup>2</sup>	-	13.3 x 6.5	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	64.90	65.00	65.10
Insertion Loss at Fo	dB	-	17.00	20.00
Group Delay Variation Fo±2.8MHz	nsec	-	50	90
Absolute Delay at Fo	usec	-	1.75	-
Passband Ripple Variation Fo±2.8MHz	dB	-	0.35	0.90
Bandwidth at -1dB	MHz	6.00	6.16	-
Bandwidth at -3dB	MHz	-	6.60	-
Bandwidth at -40dB	MHz	-	8.30	8.50
Ultimate Rejection	dB	40	47	
Temperature Coefficient	ppm/°C	-	-20	-

**Notes :** (1) With Matching Network (Ref. Testing Environment Circuit as shown below).  
Those impedances could be modified with different impedance values and/or structures, if necessary.


## Package Dimensions



- ① **TRANSKO:** Brand
- ② **TL06506B:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

## Testing Environment





Test Fixture & Values	
Input	L1 = 47 nH
Output	L2 = 56 nH
Source/Load Impedance	50 Ω

## Frequency Characteristics

### Frequency Response



**Bandwidth at -1.0 dB**

**Bandwidth at -3.0 dB**




**Bandwidth at -35.0 dB**

**Bandwidth at -40.0 dB**




**Frequency Response**


**Ripple Variation Fo±2.80MHz**



**Group Delay Variation Fo±2.80MHz**



**Smith Chart**



**SWR**

