

- 95.0 MHz IF SAW Filter / 59.40 MHz Bandwidth
- Revision 0: 20 Aug. 2008


Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operating Temperature Range	°C	-	25	-
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	V			
Length x Width	mm ²	-	13.3 x 6.5	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	94.70	-
Insertion Loss at Fo	dB	-	25.0	27.0
Temperature Coefficient	ppm/°C	-	-72	-
Amplitude Ripple within fo ±28.50 MHz	dB _{p-p}	-	0.60	1.00
Group Delay Variation within fo ±28.50 MHz	nsec	-	25	60
Absolute Delay at Fo	µsec	-	1.06	-
Bandwidth at -1.0 dB	MHz	58.80	59.40	-
Bandwidth at -3.0 dB	MHz	-	60.70	-
Bandwidth at -40.0 dB	MHz	-	66.20	67.00
Relative Attenuation:				
Lower Sidelobe	dB	-	45	-
Upper Sidelobe	dB	-	40	-

Notes : (1) With Matching Network (Ref. Testing Environment Circuit as shown below).
Those impedances could be modified with different impedance values and/or structures, if necessary.


Package Dimensions



- ① **TRANSKO:** Brand
- ② **TL09559A:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

Testing Environment




Test Fixture & Values	
Input	L1=56nH , C1=330pF
Output	L2=82nH , C2=5pF
Source/Load Impedance	50 Ω


Frequency Characteristics

Frequency Response


Bandwidth at -1.0 dB




Bandwidth at -3.0 dB



Bandwidth at -40.0 dB




Wide-Band




Frequency Response


Ripple Variation Fo±28.50MHz



Group Delay Variation Fo±28.50MHz



Smith Chart



VSWR

