

- 125.0 MHz IF SAW Filter / 16.75 MHz Bandwidth
- Revision 1: 28 Oct. 2010

## Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operating Temperature Range	°C	-30	-	85
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Load Impedance (single ended) <sup>(1)</sup>	Ω	-	50	-
Package type & size	V			
Length x Width	mm <sup>2</sup>	-	13.3 x 6.5	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	125.00	-
Insertion Loss at Fo	dB	-	13.50	15.00
Group Delay Variation at Fo ± 7.47 MHz	nsec	-	40	80
Absolute Delay at Fo	usec	-	0.92	1.00
Passband Ripple Variation at Fo ± 7.47 MHz	dB	-	0.35	0.80
Bandwidth at -1dB	MHz	16.50	16.75	-
Bandwidth at -3dB	MHz	-	17.62	-
Bandwidth at -40dB	MHz	-	20.90	21.10
Ultimate Rejection	dB	40	48	-
Temperature Coefficient	ppm/°C	-	-86	-

**Notes :** (1) With Matching Network (Ref. Testing Environment Circuit as shown below).  
Those impedances could be modified with different impedance values and/or structures, if necessary.


## Package Dimensions



- ① **TRANSKO:** Brand
- ② **TL12516A:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

## Testing Environment





Test Fixture & Values	
Input	L1 = 33nH, C1=62pF
Output	L2 = 22nH, C2=47pF
Source/Load Impedance	50 Ω

## Frequency Characteristics

### Frequency Response



**Bandwidth at -1.0 dB**

**Bandwidth at -3.0 dB**




**Bandwidth at -40.0 dB**

**Wide-Band**




## Frequency Response


**Ripple Variation Fo±7.47MHz**



**Group Delay Variation Fo±7.47MHz**



**Smith Chart**



**VSWR**

