

- 240.0 MHz IF SAW Filter / 16.91 MHz Bandwidth
- Revision 0: 29 Oct. 2009

Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operating Temperature Range	°C	-30	-	80
Storage Temperature Range	°C	-40	-	85
Maximum DC Voltage	V	-	-	10
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	V			
Length x Width	mm ²	-	13.3 x 6.5	-
Height	mm	-	-	1.8

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	240.0	-
Insertion Loss at Fo	dB	-	16.0	18.0
Group Delay Variation at Fo ± 7.5 MHz	nsec	-	24	80
Absolute Delay at Fo	usec	-	0.6	
Passband Ripple Variation at Fo ± 7.5 MHz	dB	-	0.38	1.00
Bandwidth at -1dB	-	16.60	16.91	-
Bandwidth at -3dB	MHz	-	18.26	-
Bandwidth at -40dB	MHz	-	23.30	25.50
Ultimate Rejection	dB	40	45	-
Temperature Coefficient	ppm/°C	-	-18	-

Notes : (1) With Matching Network (Ref. Testing Environment Circuit as shown below).
Those impedances could be modified with different impedance values and/or structures, if necessary.


Package Dimensions



- ① **TRANSKO:** Brand
- ② **TL24016A:** Model Name
- ③ **X :** Date Code (Year)
- ④ **Y :** Date Code (Month)
- ⑤ **Z :** Date Code (Date)
- : Index Dot

Pin Description	
A, B, C, D, F, G, H, I, J, L	Ground
K	Input
E	Output

Testing Environment




Test Fixture & Values	
Input	L1 = 12nH, C1 = 82pF
Output	L2 = 12nH, C2 = 82pF
Source/Load Impedance	50 Ω


Frequency Characteristics

Frequency Response


Bandwidth at -1.0 dB




Bandwidth at -3.0 dB



Bandwidth at -40.0 dB




Wide Band




Frequency Response

Ripple Variation Fo±7.5MHz



Group Delay Variation Fo±7.5MHz



Smith Chart



VSWR

