

- Wireless, RF SAW Filter
- Revision 0: July 2012


Electrical Characteristics

MAXIMUM RATING				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Operating Temperature Range	°C	-40	-	+85
Storage Temperature Range	°C	-50	-	+85
Maximum DC Voltage	V	-	-	0
Maximum Input Power	dBm	-	-	10
Source Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Load Impedance (single ended) ⁽¹⁾	Ω	-	50	-
Package type & size	M			
Length x Width	mm ²	-	3.0 x 3.0	-
Height	mm	-	-	1.3

ELECTRICAL SPECIFICATION				
PARAMETERS DESCRIPTION	UNIT	MINIMUM	TYPICAL	MAXIMUM
Center Frequency (Fo)	MHz	-	1569.0	-
Insertion Loss within 1553.0 ~ 1585.0 MHz	dB	-	2.2	4.0
Amplitude Ripple within 1553.0 ~ 1585.0 MHz	dB _{p-p}	-	1.0	2.5
Attenuation:				
1524.0 MHz (Fo - 45.0MHz)	dB	25	35	-
1614.0 MHz (Fo + 45.0MHz)	dB	30	50	-
VSWR within 1553.0 ~ 1585.0 MHz	-	-	2.0	2.5

Notes: (1) No Matching Network (Ref. Testing Environment Circuit as shown below).


Package Dimensions



Marking Descriptions	
d	Wireless Application
L	Series Number
X	Date Code (Year)
Y	Date Code (Month)


Pin Description	
A, C, D, F	Ground
E	In or Out
B	Out or In

Testing Environment




Source & Load Impedance: 50 Ω

Frequency Characteristics



VSWR



Smith Chart

